



## AMS 100 - SINGLE-PHASE AUTOTRANSFORMER 230-400V - 100VA - IP00



SKU: 41181  
Référence technique: 43R18

### CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer  
Current : single-phase  
Certification(s) : EN 61558-2-13  
Power : 100 VA  
Primary voltage : 230-400V reversible  
Secondary voltage : 230-400V reversible  
:  
Protection : IP00  
Version : standard  
Inrush current : less than or equal to 11 In  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 3,3 W  
Load losses : 5,5 W  
Voltage drop : 5,2 %  
UCC : 4,1 %  
Efficiency : 91,9 %

### DIMENSIONS:

Dimensions (A x B x H) : 78 x 85 x 79 mm  
Mounting centres (a x b) : 58 x 52 mm  
Mounting diameter (Ø) : 6,5x10 mm  
Weight : 1,3 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 0,5A  
Primary 230V (D circuit breaker) : 1 x 1A  
Primary 400V (aM fuse(s)) : 1 x 0,25A  
:  
Secondary 230V (gG fuse(s)) : 1 x 0,5A  
Secondary 230V (C circuit breaker(s)) : 1 x 1A  
Secondary 400V (gG fuse(s)) : 1 x 0,25A  
Secondary 400V (C circuit breaker(s)) : 1 x 1A

### OPTIONS:

Tropicalization