





AMS 2000 - SINGLE-PHASE AUTOTRANSFORMER 230-400V - 2KVA - IP00



SKU: 41351
Référence technique: 43B35

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : single-phase
Certification(s) : EN 60076
Power : 2 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP00
Version : standard
Inrush current : less than or equal to 11 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 25 W
Load losses : 45,4 W
Voltage drop : 2,2 %
UCC : 2,3 %
Efficiency : 96,6 %

DIMENSIONS:

Dimensions (A x B x H) : 153 x 130 x 135 mm
Mounting centres (a x b) : 125 x 105 mm
Mounting diameter (ø) : 9x18 mm
Weight : 9,2 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 10A
Primary 230V (D circuit breaker) : 1 x 10A
Primary 400V (aM fuse(s)) : 1 x 5A
:
Secondary 230V (gG fuse(s)) : 1 x 10A
Secondary 230V (C circuit breaker(s)) : 1 x 10A
Secondary 400V (gG fuse(s)) : 1 x 5A
Secondary 400V (C circuit breaker(s)) : 1 x 5A

OPTIONS:

Tropicalization