




AMS 630 - SINGLE-PHASE AUTOTRANSFORMER 230-400V - 630VA - IP00



SKU: 41281
Référence technique: 43R28

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : single-phase
Certification(s) : EN 61558-2-13
Power : 630 VA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP00
Version : standard
Inrush current : less than or equal to 11 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 11 W
Load losses : 18,7 W
Voltage drop : 2,9 %
UCC : 2,9 %
Efficiency : 95,5 %

DIMENSIONS:

Dimensions (A x B x H) : 122 x 110 x 109 mm
Mounting centres (a x b) : 100 x 78 mm
Mounting diameter (Ø) : 7x12 mm
Weight : 4,4 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 3,15A
Primary 230V (D circuit breaker) : 1 x 3,15A
Primary 400V (aM fuse(s)) : 1 x 1,6A
:
Secondary 230V (gG fuse(s)) : 1 x 3,15A
Secondary 230V (C circuit breaker(s)) : 1 x 3,15A
Secondary 400V (gG fuse(s)) : 1 x 1,6A
Secondary 400V (C circuit breaker(s)) : 1 x 1,6A

OPTIONS:

Tropicalization