





AMS 6300 - SINGLE-PHASE AUTOTRANSFORMER 230-400V - 6,3KVA - IP00



SKU: 41411
Référence technique: 43B41

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : single-phase
Certification(s) : EN 60076
Power : 6,3 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP00
Version : standard
Inrush current : less than or equal to 11 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 60 W
Load losses : 108 W
Voltage drop : 1,7 %
UCC : 1,4 %
Efficiency : 97,4 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 185 x 280 mm
Mounting centres (a x b) : 200 x 119 mm
Mounting diameter (ø) : 12x31 mm
Weight : 25,5 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 32A
Primary 230V (D circuit breaker) : 1 x 32A
Primary 400V (aM fuse(s)) : 1 x 16A
:
Secondary 230V (gG fuse(s)) : 1 x 32A
Secondary 230V (C circuit breaker(s)) : 1 x 32A
Secondary 400V (gG fuse(s)) : 1 x 16A
Secondary 400V (C circuit breaker(s)) : 1 x 16A

OPTIONS:

Tropicalization