





AMSP 160 - SINGLE-PHASE AUTOTRANSFORMER 230-400V - 160VA - IP21



SKU: 41215
Référence technique: 44B21

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : single-phase
Certification(s) : EN 61558-2-13
Power : 160 VA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP41-IK08
Version : standard
Inrush current : less than or equal to 11 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 4,3 W
Load losses : 7,6 W
Voltage drop : 4,5 %
UCC : 3,4 %
Efficiency : 93,1 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
Mounting centres (a x b) : 200 x 224 mm
Mounting diameter (ø) : 7x14 mm
Weight : 4,3 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 0,8A
Primary 230V (D circuit breaker) : 1 x 1A
Primary 400V (aM fuse(s)) : 1 x 0,5A
:
Secondary 230V (gG fuse(s)) : 1 x 0,8A
Secondary 230V (C circuit breaker(s)) : 1 x 1A
Secondary 400V (gG fuse(s)) : 1 x 0,5A
Secondary 400V (C circuit breaker(s)) : 1 x 1A

OPTIONS:

Tropicalization
Specific colour for the enclosure