



## AMSP 2500 - SINGLE-PHASE AUTOTRANSFORMER 230-400V - 2,5KVA - IP21



SKU: 41365  
Référence technique: 44B36

### CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer  
Current : single-phase  
Certification(s) : EN 60076  
Power : 2,5 kVA  
Primary voltage : 230-400V reversible  
Secondary voltage : 230-400V reversible  
:  
Protection : IP41-IK08  
Version : standard  
Inrush current : less than or equal to 11 In  
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 31 W  
Load losses : 54 W  
Voltage drop : 2,1 %  
UCC : 1,8 %  
Efficiency : 96,7 %

### DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm  
Mounting centres (a x b) : 200 x 224 mm  
Mounting diameter (ø) : 7x14 mm  
Weight : 14,4 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 12A  
Primary 230V (D circuit breaker) : 1 x 12A  
Primary 400V (aM fuse(s)) : 1 x 6,3A  
:  
Secondary 230V (gG fuse(s)) : 1 x 12A  
Secondary 230V (C circuit breaker(s)) : 1 x 12A  
Secondary 400V (gG fuse(s)) : 1 x 6,3A  
Secondary 400V (C circuit breaker(s)) : 1 x 6,3A

### OPTIONS:

Tropicalization  
Specific colour for the enclosure