



## AMSP 2500 - SINGLE-PHASE AUTOTRANSFORMER 230-400V - 2,5KVA - IP21



SKU: 41365  
 Référence technique: 44B36

### CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer  
 Current : single-phase  
 Certification(s) : EN 60076  
 Power : 2,5 kVA  
 Primary voltage : 230-400V reversible  
 Secondary voltage : 230-400V reversible  
 :  
 Protection : IP41-IK08  
 Version : standard  
 Inrush current : less than or equal to 11 In  
 Heatings : F (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 31 W  
 Load losses : 54 W  
 Voltage drop : 2,1 %  
 UCC : 1,8 %  
 Efficiency : 96,7 %

### DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm  
 Mounting centres (a x b) : 200 x 224 mm  
 Mounting diameter (∅) : 7x14 mm  
 Weight : 14,4 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 12A  
 Primary 230V (D circuit breaker) : 1 x 12A  
 Primary 400V (aM fuse(s)) : 1 x 6,3A  
 :  
 Secondary 230V (gG fuse(s)) : 1 x 12A  
 Secondary 230V (C circuit breaker(s)) : 1 x 12A  
 Secondary 400V (gG fuse(s)) : 1 x 6,3A  
 Secondary 400V (C circuit breaker(s)) : 1 x 6,3A

### OPTIONS:

Tropicalization  
 Specific colour for the enclosure