


AMSP 3200 - SINGLE-PHASE AUTOTRANSFORMER 230-400V - 3,15KVA - IP21



SKU: 41385
Référence technique: 44B38

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : single-phase
Certification(s) : EN 60076
Power : 3,15 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP41-IK08
Version : standard
Inrush current : less than or equal to 11 In
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 38 W
Load losses : 64,4 W
Voltage drop : 2 %
UCC : 1,9 %
Efficiency : 96,9 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
Mounting centres (a x b) : 200 x 224 mm
Mounting diameter (Ø) : 7x14 mm
Weight : 17 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 16A
Primary 230V (D circuit breaker) : 1 x 16A
Primary 400V (aM fuse(s)) : 1 x 8A
:
Secondary 230V (gG fuse(s)) : 1 x 16A
Secondary 230V (C circuit breaker(s)) : 1 x 16A
Secondary 400V (gG fuse(s)) : 1 x 8A
Secondary 400V (C circuit breaker(s)) : 1 x 8A

OPTIONS:

Tropicalization
Specific colour for the enclosure