





ATS 1600 - THREE-PHASE AUTOTRANSFORMER 230-400V - 1600VA - IP00



SKU: 42341
 Référence technique: 48R34

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
 Current : three-phase
 Certification(s) : EN 61558-2-13
 Power : 1600 VA
 Primary voltage : 230-400V reversible
 Secondary voltage : 230-400V reversible
 :
 Protection : IP00
 Version : standard
 Inrush current : less than or equal to 11 In
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 18 W
 Load losses : 51 W
 Voltage drop : 3,1 %
 UCC : 2,2 %
 Efficiency : 95,9 %

DIMENSIONS:

Dimensions (A x B x H) : 180 x 100 x 175 mm
 Mounting centres (a x b) : 150 x 75 mm
 Mounting diameter (ø) : 8x18 mm
 Weight : 9 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 4A
 Primary 230V (D circuit breaker) : 3 x 4A
 Primary 400V (aM fuse(s)) : 3 x 2,5A
 :
 Secondary 230V (gG fuse(s)) : 4 x 4A
 Secondary 230V (C circuit breaker(s)) : 4 x 4A
 Secondary 400V (gG fuse(s)) : 4 x 2,5A
 Secondary 400V (C circuit breaker(s)) : 4 x 2,5A

OPTIONS:

Tropicalization