




ATS 16000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 16KVA - IP00



SKU: 42451
 Référence technique: 48B45

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 16 kVA
 Primary voltage : 230-400V reversible
 Secondary voltage : 230-400V reversible
 :
 Protection : IP00
 Version : standard
 Inrush current : less than or equal to 5 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 85 W
 Load losses : 425 W
 Voltage drop : 2,6 %
 UCC : 2,8 %
 Efficiency : 96,9 %

DIMENSIONS:

Dimensions (A x B x H) : 420 x 205 x 330 mm
 Mounting centres (a x b) : 330 x 140 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 44 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 40A
 Primary 230V (D circuit breaker) : 3 x 40A
 Primary 400V (aM fuse(s)) : 3 x 25A
 :
 Secondary 230V (gG fuse(s)) : 4 x 40A
 Secondary 230V (C circuit breaker(s)) : 4 x 40A
 Secondary 400V (gG fuse(s)) : 4 x 25A
 Secondary 400V (C circuit breaker(s)) : 4 x 25A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Running wheels