


ATS 16000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 16KVA - IP00



SKU: 42451
Référence technique: 48B45

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 60076
Power : 16 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP00
Version : standard
Inrush current : less than or equal to 5 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 85 W
Load losses : 425 W
Voltage drop : 2,6 %
UCC : 2,8 %
Efficiency : 96,9 %

DIMENSIONS:

Dimensions (A x B x H) : 420 x 205 x 330 mm
Mounting centres (a x b) : 330 x 140 mm
Mounting diameter (ø) : 11x22 mm
Weight : 44 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 40A
Primary 230V (D circuit breaker) : 3 x 40A
Primary 400V (aM fuse(s)) : 3 x 25A
:
Secondary 230V (gG fuse(s)) : 4 x 40A
Secondary 230V (C circuit breaker(s)) : 4 x 40A
Secondary 400V (gG fuse(s)) : 4 x 25A
Secondary 400V (C circuit breaker(s)) : 4 x 25A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels