




ATS 160000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 160KVA - IP00



SKU: 42551
Référence technique: 48B55

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 60076
Power : 160 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP00
Version : standard
Inrush current : less than or equal to 5 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 480 W
Load losses : 1820 W
Voltage drop : 1,1 %
UCC : 1,6 %
Efficiency : 98,6 %

DIMENSIONS:

Dimensions (A x B x H) : 600 x 370 x 610 mm
Mounting centres (a x b) : 470 x 340 mm
Mounting diameter (ø) : 11x22 mm
Weight : 215 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 315A
Primary 230V (D circuit breaker) : 3 x 315A
Primary 400V (aM fuse(s)) : 3 x 200A
:
Secondary 230V (gG fuse(s)) : 4 x 315A
Secondary 230V (C circuit breaker(s)) : 4 x 315A
Secondary 400V (gG fuse(s)) : 4 x 200A
Secondary 400V (C circuit breaker(s)) : 4 x 200A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels