




ATS 2000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 2KVA - IP00



SKU: 42351
Référence technique: 48R35

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 61558-2-13
Power : 2 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP00
Version : standard
Inrush current : less than or equal to 11 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 22 W
Load losses : 63 W
Voltage drop : 3,1 %
UCC : 2,3 %
Efficiency : 95,9 %

DIMENSIONS:

Dimensions (A x B x H) : 180 x 110 x 175 mm
Mounting centres (a x b) : 150 x 85 mm
Mounting diameter (ø) : 8x18 mm
Weight : 10,4 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 5A
Primary 230V (D circuit breaker) : 3 x 5A
Primary 400V (aM fuse(s)) : 3 x 3,15A
:
Secondary 230V (gG fuse(s)) : 4 x 5A
Secondary 230V (C circuit breaker(s)) : 4 x 5A
Secondary 400V (gG fuse(s)) : 4 x 3,15A
Secondary 400V (C circuit breaker(s)) : 4 x 3,15A

OPTIONS:

Tropicalization