


ATS 250 - THREE-PHASE AUTOTRANSFORMER 230-400V - 250VA - IP00



SKU: 42231
Référence technique: 48R23

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 61558-2-13
Power : 250 VA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP00
Version : standard
Inrush current : less than or equal to 11 I_n
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 4,1 W
Load losses : 17 W
Voltage drop : 6,4 %
UCC : 4,4 %
Efficiency : 92,2 %

DIMENSIONS:

Dimensions (A x B x H) : 150 x 61 x 125 mm
Mounting centres (a x b) : 100 x 42,5 mm
Mounting diameter (ø) : 6x13 mm
Weight : 2,3 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 0,63A
Primary 230V (D circuit breaker) : 3 x 0,63A
Primary 400V (aM fuse(s)) : 3 x 0,5A
:
Secondary 230V (gG fuse(s)) : 4 x 0,63A
Secondary 230V (C circuit breaker(s)) : 4 x 0,63A
Secondary 400V (gG fuse(s)) : 4 x 0,5A
Secondary 400V (C circuit breaker(s)) : 4 x 0,5A

OPTIONS:

Tropicalization