




## ATS 2500 - THREE-PHASE AUTOTRANSFORMER 230-400V - 2,5KVA - IP00



SKU: 42361  
Référence technique: 48R36

### CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer  
Current : three-phase  
Certification(s) : EN 61558-2-13  
Power : 2,5 kVA  
Primary voltage : 230-400V reversible  
Secondary voltage : 230-400V reversible  
:  
Protection : IP00  
Version : standard  
Inrush current : less than or equal to 11 In  
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 26 W  
Load losses : 79,5 W  
Voltage drop : 3,1 %  
UCC : 2,1 %  
Efficiency : 96 %

### DIMENSIONS:

Dimensions (A x B x H) : 180 x 120 x 175 mm  
Mounting centres (a x b) : 150 x 95 mm  
Mounting diameter (ø) : 8x18 mm  
Weight : 11,8 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 6,3A  
Primary 230V (D circuit breaker) : 3 x 6,3A  
Primary 400V (aM fuse(s)) : 3 x 4A  
:  
Secondary 230V (gG fuse(s)) : 4 x 6,3A  
Secondary 230V (C circuit breaker(s)) : 4 x 6,3A  
Secondary 400V (gG fuse(s)) : 4 x 4A  
Secondary 400V (C circuit breaker(s)) : 4 x 4A

### OPTIONS:

Tropicalization