





ATS 400 - THREE-PHASE AUTOTRANSFORMER 230-400V - 400VA - IP00



SKU: 42261
Référence technique: 48R26

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 61558-2-13
Power : 400 VA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP00
Version : standard
Inrush current : less than or equal to 11 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 7,8 W
Load losses : 20 W
Voltage drop : 4,8 %
UCC : 3,3 %
Efficiency : 93,5 %

DIMENSIONS:

Dimensions (A x B x H) : 150 x 80 x 125 mm
Mounting centres (a x b) : 100 x 61,5 mm
Mounting diameter (ø) : 6x13 mm
Weight : 3,7 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 1A
Primary 230V (D circuit breaker) : 3 x 1A
Primary 400V (aM fuse(s)) : 3 x 0,63A
:
Secondary 230V (gG fuse(s)) : 4 x 1A
Secondary 230V (C circuit breaker(s)) : 4 x 1A
Secondary 400V (gG fuse(s)) : 4 x 0,63A
Secondary 400V (C circuit breaker(s)) : 4 x 0,63A

OPTIONS:

Tropicalization