




## ATS 400 - THREE-PHASE AUTOTRANSFORMER 230-400V - 400VA - IP00



SKU: 42261  
Référence technique: 48R26

### CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer  
Current : three-phase  
Certification(s) : EN 61558-2-13  
Power : 400 VA  
Primary voltage : 230-400V reversible  
Secondary voltage : 230-400V reversible  
:  
Protection : IP00  
Version : standard  
Inrush current : less than or equal to 11 In  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 7,8 W  
Load losses : 20 W  
Voltage drop : 4,8 %  
UCC : 3,3 %  
Efficiency : 93,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 150 x 80 x 125 mm  
Mounting centres (a x b) : 100 x 61,5 mm  
Mounting diameter (ø) : 6x13 mm  
Weight : 3,7 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 1A  
Primary 230V (D circuit breaker) : 3 x 1A  
Primary 400V (aM fuse(s)) : 3 x 0,63A  
:  
Secondary 230V (gG fuse(s)) : 4 x 1A  
Secondary 230V (C circuit breaker(s)) : 4 x 1A  
Secondary 400V (gG fuse(s)) : 4 x 0,63A  
Secondary 400V (C circuit breaker(s)) : 4 x 0,63A

### OPTIONS:

Tropicalization