


ATS 4000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 4KVA - IP00



SKU: 42391
Référence technique: 48R39

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 61558-2-13
Power : 4 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP00
Version : standard
Inrush current : less than or equal to 11 In
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 39 W
Load losses : 116 W
Voltage drop : 2,8 %
UCC : 1,9 %
Efficiency : 96,3 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 120 x 230 mm
Mounting centres (a x b) : 200 x 90 mm
Mounting diameter (ø) : 8x18 mm
Weight : 18 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 10A
Primary 230V (D circuit breaker) : 3 x 10A
Primary 400V (aM fuse(s)) : 3 x 6,3A
:
Secondary 230V (gG fuse(s)) : 4 x 10A
Secondary 230V (C circuit breaker(s)) : 4 x 10A
Secondary 400V (gG fuse(s)) : 4 x 6,3A
Secondary 400V (C circuit breaker(s)) : 4 x 6,3A

OPTIONS:

Tropicalization