




ATS 630 - THREE-PHASE AUTOTRANSFORMER 230-400V - 630VA - IP00



SKU: 42281
 Référence technique: 48R28

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
 Current : three-phase
 Certification(s) : EN 61558-2-13
 Power : 630 VA
 Primary voltage : 230-400V reversible
 Secondary voltage : 230-400V reversible
 :
 Protection : IP00
 Version : standard
 Inrush current : less than or equal to 11 In
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 9,5 W
 Load losses : 25,5 W
 Voltage drop : 3,9 %
 UCC : 2,9 %
 Efficiency : 94,7 %

DIMENSIONS:

Dimensions (A x B x H) : 150 x 90 x 150 mm
 Mounting centres (a x b) : 100 x 71,5 mm
 Mounting diameter (Ø) : 6x13 mm
 Weight : 4,7 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 1,6A
 Primary 230V (D circuit breaker) : 3 x 1,6A
 Primary 400V (aM fuse(s)) : 3 x 31A
 :
 Secondary 230V (gG fuse(s)) : 4 x 1,6A
 Secondary 230V (C circuit breaker(s)) : 4 x 1,6A
 Secondary 400V (gG fuse(s)) : 4 x 31A
 Secondary 400V (C circuit breaker(s)) : 4 x 31A

OPTIONS:

Tropicalization