





ATS 6300 - THREE-PHASE AUTOTRANSFORMER 230-400V - 6,3KVA - IP00



SKU: 42411
 Référence technique: 48B41

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 6,3 kVA
 Primary voltage : 230-400V reversible
 Secondary voltage : 230-400V reversible
 :
 Protection : IP00
 Version : standard
 Inrush current : less than or equal to 11 In
 Heatings : F (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 59 W
 Load losses : 129 W
 Voltage drop : 2 %
 UCC : 1,4 %
 Efficiency : 97,1 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 145 x 230 mm
 Mounting centres (a x b) : 200 x 115 mm
 Mounting diameter (ø) : 8x18 mm
 Weight : 26,5 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 16A
 Primary 230V (D circuit breaker) : 3 x 16A
 Primary 400V (aM fuse(s)) : 3 x 10A
 :
 Secondary 230V (gG fuse(s)) : 4 x 16A
 Secondary 230V (C circuit breaker(s)) : 4 x 16A
 Secondary 400V (gG fuse(s)) : 4 x 10A
 Secondary 400V (C circuit breaker(s)) : 4 x 10A

OPTIONS:

Tropicalization