




## ATS 63000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 63KVA - IP00



SKU: 42511  
 Référence technique: 48B51

### CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 63 kVA  
 Primary voltage : 230-400V reversible  
 Secondary voltage : 230-400V reversible  
 :  
 Protection : IP00  
 Version : Autotransformer (standard)  
 Inrush current : less than or equal to 5 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 40°C  
 No load losses : 240 W  
 Load losses : 1020 W  
 Voltage drop : 1,6 %  
 UCC : 1,9 %  
 Efficiency : 98 %

### DIMENSIONS:

Dimensions (A x B x H) : 490 x 265 x 470 mm  
 Mounting centres (a x b) : 395 x 235 mm  
 Mounting diameter (ø) : 11x22 mm  
 Weight : 117 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 160A  
 Primary 230V (D circuit breaker) : 3 x 160A  
 Primary 400V (aM fuse(s)) : 3 x 100A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 160A  
 Secondary 230V (C circuit breaker(s)) : 4 x 160A  
 Secondary 400V (gG fuse(s)) : 4 x 100A  
 Secondary 400V (C circuit breaker(s)) : 4 x 100A

### OPTIONS:

Tropicalization  
 Vibration isolating mount  
 Running wheels