



ATS 8000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 8KVA - IP00



SKU: 42421
Référence technique: 48B42

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 60076
Power : 8 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP00
Version : standard
Inrush current : less than or equal to 11 In
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 73 W
Load losses : 163 W
Voltage drop : 2 %
UCC : 1,4 %
Efficiency : 97,1 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 145 x 280 mm
Mounting centres (a x b) : 250 x 100 mm
Mounting diameter (ø) : 8,5x20 mm
Weight : 31,5 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 20A
Primary 230V (D circuit breaker) : 3 x 20A
Primary 400V (aM fuse(s)) : 3 x 12A
:
Secondary 230V (gG fuse(s)) : 4 x 20A
Secondary 230V (C circuit breaker(s)) : 4 x 20A
Secondary 400V (gG fuse(s)) : 4 x 12A
Secondary 400V (C circuit breaker(s)) : 4 x 12A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels