


ATS 80000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 80KVA - IP00



SKU: 42521
Référence technique: 48B52

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 60076
Power : 80 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP00
Version : Autotransformer (standard)
Inrush current : less than or equal to 5 I_n
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 280 W
Load losses : 1180 W
Voltage drop : 1,5 %
UCC : 1,8 %
Efficiency : 98,2 %

DIMENSIONS:

Dimensions (A x B x H) : 490 x 370 x 530 mm
Mounting centres (a x b) : 395 x 340 mm
Mounting diameter (∅) : 11x22 mm
Weight : 140 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 200A
Primary 230V (D circuit breaker) : 3 x 200A
Primary 400V (aM fuse(s)) : 3 x 125A
:
Secondary 230V (gG fuse(s)) : 4 x 200A
Secondary 230V (C circuit breaker(s)) : 4 x 200A
Secondary 400V (gG fuse(s)) : 4 x 125A
Secondary 400V (C circuit breaker(s)) : 4 x 125A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels