



ATSP 10000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 10KVA - IP21



SKU: 42435
 Référence technique: 49B43

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 10 kVA
 Primary voltage : 230-400V reversible
 Secondary voltage : 230-400V reversible
 :
 Protection : IP21-IK08
 Version : standard
 Inrush current : less than or equal to 11 In
 Heatings : F (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 86 W
 Load losses : 170 W
 Voltage drop : 1,7 %
 UCC : 1,2 %
 Efficiency : 97,5 %

DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm
 Mounting centres (a x b) : 250 x 340 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 49,4 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 25A
 Primary 230V (D circuit breaker) : 3 x 25A
 Primary 400V (aM fuse(s)) : 3 x 16A
 :
 Secondary 230V (gG fuse(s)) : 4 x 25A
 Secondary 230V (C circuit breaker(s)) : 4 x 25A
 Secondary 400V (gG fuse(s)) : 4 x 16A
 Secondary 400V (C circuit breaker(s)) : 4 x 16A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Running wheels
 Factory assembled and wired primary and secondary protections
 Specific colour for the enclosure