




## ATSP 1600 - THREE-PHASE AUTOTRANSFORMER 230-400V - 1600VA - IP21



SKU: 42345  
Référence technique: 49R34

### CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer  
Current : three-phase  
Certification(s) : EN 61558-2-13  
Power : 1600 VA  
Primary voltage : 230-400V reversible  
Secondary voltage : 230-400V reversible  
:  
Protection : IP41-IK08  
Version : standard  
Inrush current : less than or equal to 11 In  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 18 W  
Load losses : 51 W  
Voltage drop : 3,1 %  
UCC : 2,2 %  
Efficiency : 95,9 %

### DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm  
Mounting centres (a x b) : 200 x 224 mm  
Mounting diameter (ø) : 7x14 mm  
Weight : 11,6 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 4A  
Primary 230V (D circuit breaker) : 3 x 4A  
Primary 400V (aM fuse(s)) : 3 x 2,5A  
:  
Secondary 230V (gG fuse(s)) : 4 x 4A  
Secondary 230V (C circuit breaker(s)) : 4 x 4A  
Secondary 400V (gG fuse(s)) : 4 x 2,5A  
Secondary 400V (C circuit breaker(s)) : 4 x 2,5A

### OPTIONS:

Tropicalization  
Specific colour for the enclosure