




## ATSP 16000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 16KVA - IP21



SKU: 42455  
 Référence technique: 49B45

### CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 16 kVA  
 Primary voltage : 230-400V reversible  
 Secondary voltage : 230-400V reversible  
 :  
 Protection : IP21-IK08  
 Version : standard  
 Inrush current : less than or equal to 5 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 85 W  
 Load losses : 425 W  
 Voltage drop : 2,6 %  
 UCC : 2,8 %  
 Efficiency : 96,9 %

### DIMENSIONS:

Dimensions (A x B x H) : 580 x 370 x 600 mm  
 Mounting centres (a x b) : 330 x 340 mm  
 Mounting diameter (ø) : 11x22 mm  
 Weight : 57 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 40A  
 Primary 230V (D circuit breaker) : 3 x 40A  
 Primary 400V (aM fuse(s)) : 3 x 25A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 40A  
 Secondary 230V (C circuit breaker(s)) : 4 x 40A  
 Secondary 400V (gG fuse(s)) : 4 x 25A  
 Secondary 400V (C circuit breaker(s)) : 4 x 25A

### OPTIONS:

Tropicalization  
 Vibration isolating mount  
 Running wheels  
 Factory assembled and wired primary and secondary protections  
 Specific colour for the enclosure