




## ATSP 200000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 200KVA - IP21



SKU: 42565  
Référence technique: 49B56

### CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 200 kVA  
Primary voltage : 230-400V reversible  
Secondary voltage : 230-400V reversible  
:  
Protection : IP21-IK08  
Version : standard  
Inrush current : less than or equal to 5 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 580 W  
Load losses : 1940 W  
Voltage drop : 1 %  
UCC : 1,6 %  
Efficiency : 98,8 %

### DIMENSIONS:

Dimensions (A x B x H) : 800 x 520 x 980 mm  
Mounting centres (a x b) : 570 x 490 mm  
Mounting diameter (ø) : 11x22 mm  
Weight : 345 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 500A  
Primary 230V (D circuit breaker) : 3 x 500A  
Primary 400V (aM fuse(s)) : 3 x 315A  
:  
Secondary 230V (gG fuse(s)) : 4 x 500A  
Secondary 230V (C circuit breaker(s)) : 4 x 500A  
Secondary 400V (gG fuse(s)) : 4 x 315A  
Secondary 400V (C circuit breaker(s)) : 4 x 315A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels  
Factory assembled and wired primary and secondary protections  
Specific colour for the enclosure