


ATSP 2500 - THREE-PHASE AUTOTRANSFORMER 230-400V - 2,5KVA - IP21



SKU: 42365
 Référence technique: 49R36

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
 Current : three-phase
 Certification(s) : EN 61558-2-13
 Power : 2,5 kVA
 Primary voltage : 230-400V reversible
 Secondary voltage : 230-400V reversible
 :
 Protection : IP41-IK08
 Version : standard
 Inrush current : less than or equal to 11 In
 Heatings : F (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 26 W
 Load losses : 79,5 W
 Voltage drop : 3,1 %
 UCC : 2,1 %
 Efficiency : 96 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
 Mounting centres (a x b) : 200 x 224 mm
 Mounting diameter (ø) : 7x14 mm
 Weight : 14,4 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 6,3A
 Primary 230V (D circuit breaker) : 3 x 6,3A
 Primary 400V (aM fuse(s)) : 3 x 4A
 :
 Secondary 230V (gG fuse(s)) : 4 x 6,3A
 Secondary 230V (C circuit breaker(s)) : 4 x 6,3A
 Secondary 400V (gG fuse(s)) : 4 x 4A
 Secondary 400V (C circuit breaker(s)) : 4 x 4A

OPTIONS:

Tropicalization
 Specific colour for the enclosure