



ATSP 250000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 250KVA - IP21



SKU: 42575
Référence technique: 49B57

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 60076
Power : 250 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP21-IK08
Version : standard
Inrush current : less than or equal to 5 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 555 W
Load losses : 2840 W
Voltage drop : 1,1 %
UCC : 2 %
Efficiency : 98,7 %

DIMENSIONS:

Dimensions (A x B x H) : 960 x 820 x 930 mm
Mounting centres (a x b) : 620 x 770 mm
Mounting diameter (Ø) : 14 mm
Weight : 404 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 630A
Primary 230V (D circuit breaker) : 3 x 630A
Primary 400V (aM fuse(s)) : 3 x 400A
:
Secondary 230V (gG fuse(s)) : 4 x 630A
Secondary 230V (C circuit breaker(s)) : 4 x 630A
Secondary 400V (gG fuse(s)) : 4 x 400A
Secondary 400V (C circuit breaker(s)) : 4 x 400A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure