
**ATSP 3150 - THREE-PHASE
AUTOTRANSFORMER 230-400V -
3,15KVA - IP21**SKU: 42385
Référence technique: 49R38**CARACTÉRISTIQUES TECHNIQUES:**

Type : Autotransformer
Current : three-phase
Certification(s) : EN 61558-2-13
Power : 3,15 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP41-IK08
Version : standard
Inrush current : less than or equal to 11 In
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 33 W
Load losses : 82 W
Voltage drop : 2,5 %
UCC : 1,9 %
Efficiency : 96,5 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 290 x 300 mm
Mounting centres (a x b) : 250 x 274 mm
Mounting diameter (ø) : 7x14 mm
Weight : 18,6 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 8A
Primary 230V (D circuit breaker) : 3 x 8A
Primary 400V (aM fuse(s)) : 3 x 5A
:
Secondary 230V (gG fuse(s)) : 4 x 8A
Secondary 230V (C circuit breaker(s)) : 4 x 8A
Secondary 400V (gG fuse(s)) : 4 x 5A
Secondary 400V (C circuit breaker(s)) : 4 x 5A

OPTIONS:

Tropicalization
Specific colour for the enclosure