



ATSP 315000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 315KVA - IP21



SKU: 42585
Référence technique: 49B58

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 60076
Power : 315 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP21-IK08
Version : standard
Inrush current : less than or equal to 5 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 595 W
Load losses : 3195 W
Voltage drop : 1 %
UCC : 2,1 %
Efficiency : 98,8 %

DIMENSIONS:

Dimensions (A x B x H) : 960 x 820 x 930 mm
Mounting centres (a x b) : 620 x 770 mm
Mounting diameter (Ø) : 14 mm
Weight : 430 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 800A
Primary 230V (D circuit breaker) : 3 x 800A
Primary 400V (aM fuse(s)) : 3 x 500A
:
Secondary 230V (gG fuse(s)) : 4 x 800A
Secondary 230V (C circuit breaker(s)) : 4 x 800A
Secondary 400V (gG fuse(s)) : 4 x 500A
Secondary 400V (C circuit breaker(s)) : 4 x 500A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure