



ATSP 40000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 40KVA - IP21



SKU: 42495
Référence technique: 49B49

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 60076
Power : 40 kVA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP21-IK08
Version : Autotransformer (standard)
Inrush current : less than or equal to 5 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 175 W
Load losses : 870 W
Voltage drop : 2,1 %
UCC : 2,4 %
Efficiency : 97,5 %

DIMENSIONS:

Dimensions (A x B x H) : 580 x 370 x 600 mm
Mounting centres (a x b) : 395 x 340 mm
Mounting diameter (ø) : 11x22 mm
Weight : 99 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 100A
Primary 230V (D circuit breaker) : 3 x 100A
Primary 400V (aM fuse(s)) : 3 x 63A
:
Secondary 230V (gG fuse(s)) : 4 x 100A
Secondary 230V (C circuit breaker(s)) : 4 x 100A
Secondary 400V (gG fuse(s)) : 4 x 63A
Secondary 400V (C circuit breaker(s)) : 4 x 63A

OPTIONS:

Tropicalization
Vibration isolating mount
Running wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure