




ATSP 50000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 50KVA - IP21



SKU: 42505
 Référence technique: 49B50

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 50 kVA
 Primary voltage : 230-400V reversible
 Secondary voltage : 230-400V reversible
 :
 Protection : IP21-IK08
 Version : Autotransformer (standard)
 Inrush current : less than or equal to 5 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 200 W
 Load losses : 950 W
 Voltage drop : 1,9 %
 UCC : 2,1 %
 Efficiency : 97,8 %

DIMENSIONS:

Dimensions (A x B x H) : 580 x 370 x 600 mm
 Mounting centres (a x b) : 395 x 340 mm
 Mounting diameter (Ø) : 11x22 mm
 Weight : 112 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 125A
 Primary 230V (D circuit breaker) : 3 x 125A
 Primary 400V (aM fuse(s)) : 3 x 80A
 :
 Secondary 230V (gG fuse(s)) : 4 x 125A
 Secondary 230V (C circuit breaker(s)) : 4 x 125A
 Secondary 400V (gG fuse(s)) : 4 x 80A
 Secondary 400V (C circuit breaker(s)) : 4 x 80A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Running wheels
 Factory assembled and wired primary and secondary protections
 Specific colour for the enclosure