




ATSP 630 - THREE-PHASE AUTOTRANSFORMER 230-400V - 630VA - IP21



SKU: 42285
Référence technique: 49R28

CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer
Current : three-phase
Certification(s) : EN 61558-2-13
Power : 630 VA
Primary voltage : 230-400V reversible
Secondary voltage : 230-400V reversible
:
Protection : IP41-IK08
Version : standard
Inrush current : less than or equal to 11 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 9,5 W
Load losses : 25,5 W
Voltage drop : 3,9 %
UCC : 2,9 %
Efficiency : 94,7 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
Mounting centres (a x b) : 200 x 224 mm
Mounting diameter (ø) : 7x14 mm
Weight : 7,3 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 1,6A
Primary 230V (D circuit breaker) : 3 x 1,6A
Primary 400V (aM fuse(s)) : 3 x 31A
:
Secondary 230V (gG fuse(s)) : 4 x 1,6A
Secondary 230V (C circuit breaker(s)) : 4 x 1,6A
Secondary 400V (gG fuse(s)) : 4 x 31A
Secondary 400V (C circuit breaker(s)) : 4 x 31A

OPTIONS:

Tropicalization
Specific colour for the enclosure