



## ATSP 8000 - THREE-PHASE AUTOTRANSFORMER 230-400V - 8KVA - IP21



SKU: 42425  
 Référence technique: 49B42

### CARACTÉRISTIQUES TECHNIQUES:

Type : Autotransformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 8 kVA  
 Primary voltage : 230-400V reversible  
 Secondary voltage : 230-400V reversible  
 :  
 Protection : IP21-IK08  
 Version : standard  
 Inrush current : less than or equal to 11 In  
 Heatings : F (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 73 W  
 Load losses : 163 W  
 Voltage drop : 2 %  
 UCC : 1,4 %  
 Efficiency : 97,1 %

### DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm  
 Mounting centres (a x b) : 250 x 340 mm  
 Mounting diameter (Ø) : 11x22 mm  
 Weight : 41,5 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 3 x 20A  
 Primary 230V (D circuit breaker) : 3 x 20A  
 Primary 400V (aM fuse(s)) : 3 x 12A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 20A  
 Secondary 230V (C circuit breaker(s)) : 4 x 20A  
 Secondary 400V (gG fuse(s)) : 4 x 12A  
 Secondary 400V (C circuit breaker(s)) : 4 x 12A

### OPTIONS:

Tropicalization  
 Vibration isolating mount  
 Running wheels  
 Factory assembled and wired primary and secondary protections  
 Specific colour for the enclosure