





EUR252 - SAFETY & SEPARATION TRANSFORMER 230-400/2X24V - 250VA - IP00



SKU: 12231
Référence technique: S03Q23LV00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-6
Power : 250 VA
Primary voltage : 230-400V
Secondary voltage : 2x24V (24-48V)
:
Protection : IP00
Version : safety & circuits separation
Inrush current : less than or equal to 25 In
Heatings : B (IEC60085)
Max. ambient T° : 35°C
No load losses : 8,9 W
Load losses : 12,6 W
Voltage drop : 4,8 %
UCC : 4,2 %
Efficiency : 92,1 %

DIMENSIONS:

Dimensions (A x B x H) : 122 x 109 x 108 mm
Mounting centres (a x b) : 100 x 90 mm
Mounting diameter (ø) : 7x14 mm
Weight : 5,2 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 2,5A
Primary 230V (D circuit breaker) : 1 x 2,5A
Primary 400V (aM fuse(s)) : 1 x 1,6A
:
Secondary 24V : 1 x 10A
Secondary 48V : 1 x 6,3A

OPTIONS:

No options found.