





EUR2502 - SAFETY & SEPARATION TRANSFORMER 230-400/2X24V - 2,5KVA - IP00



SKU: 12361
Référence technique: S03Q36LV00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-6
Power : 2,5 kVA
Primary voltage : 230-400V
Secondary voltage : 2x24V (24-48V)
:
Protection : IP00
Version : safety & circuits separation
Inrush current : less than or equal to 25 In
Heatings : F (IEC60085)
Max. ambient T° : 35°C
No load losses : 40,2 W
Load losses : 106,8 W
Voltage drop : 4,1 %
UCC : 4,3 %
Efficiency : 94,4 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 190 x 275 mm
Mounting centres (a x b) : 200 x 125 mm
Mounting diameter (ø) : 12x32 mm
Weight : 26,6 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 25A
Primary 230V (D circuit breaker) : 1 x 25A
Primary 400V (aM fuse(s)) : 1 x 16A
:
Secondary 24V : 1 x 100A
Secondary 48V : 1 x 50A

OPTIONS:

No options found.