



EURM41 - SINGLE-PHASE TRANSFORMER MULTI- VOLTAGE/2X115V - 40VA - IP00



SKU: 15141
Référence technique: S03F159J00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-4, UL C22.2, CSA 5085-1
Power : 40 VA
Primary voltage : multi-voltage (215-230-245-380-400-415-440-460-480)
Secondary voltage : 2x115V (115-230V)
:
Protection : IP00
Version : Transformer (UL-CSA certified circuits separation)
Inrush current : less than or equal to 25 In
Heatings : 155°C
Max. ambient T° : 40°C
No load losses : 2,9 W
Load losses : 4,7 W
Voltage drop : 10,5 %
UCC : 7,9 %
Efficiency : 84 %

DIMENSIONS:

Dimensions (A x B x H) : 78 x 105 x 95 mm
Mounting centres (a x b) : 52 x 55 mm
Mounting diameter (Ø) : 6 x 14 mm
Weight : 1,4 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 0,5A
Primary 230V (D circuit breaker) : 1 x 1A
Primary 400V (aM fuse(s)) : 1 x 0,25A
:
Secondary 230V : 1 x 0,16A
Other voltages : N.C.

OPTIONS:

No options found.