




EURM401 - SINGLE-PHASE TRANSFORMER MULTI- VOLTAGE/2X115V - 400VA - IP00



SKU: 15261
Référence technique: S03F269J00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-4, UL C22.2, CSA 5085-1
Power : 400 VA
Primary voltage : multi-voltage (215-230-245-380-400-415-440-460-480)
Secondary voltage : 2x115V (115-230V)
:
Protection : IP00
Version : Transformer (UL-CSA certified circuits separation)
Inrush current : less than or equal to 25 In
Heatings : 155°C
Max. ambient T° : 40°C
No load losses : 10,5 W
Load losses : 35,1 W
Voltage drop : 8,1 %
UCC : 6,2 %
Efficiency : 89,8 %

DIMENSIONS:

Dimensions (A x B x H) : 125 x 125 x 125 mm
Mounting centres (a x b) : 100 x 85 mm
Mounting diameter (ø) : 7 x 14 mm
Weight : 5,7 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 4A
Primary 230V (D circuit breaker) : 1 x 4A
Primary 400V (aM fuse(s)) : 1 x 2A
:
Secondary 230V : 1 x 1,6A
Other voltages : N.C.

OPTIONS:

No options found.