




C  US



EURM2001 - SINGLE-PHASE TRANSFORMER MULTI- VOLTAGE/2X115V - 2KVA - IP00



SKU: 15351
Référence technique: S03F359J00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-4, UL C22.2, CSA 5085-1
Power : 2 kVA
Primary voltage : multi-voltage (215-230-245-380-400-415-440-460-480)
Secondary voltage : 2x115V (115-230V)
:
Protection : IP00
Version : Transformer (UL-CSA certified circuits separation)
Inrush current : less than or equal to 25 I_n
Heatings : 155°C
Max. ambient T° : 40°C
No load losses : 43,2 W
Load losses : 106 W
Voltage drop : 5 %
UCC : 4 %
Efficiency : 93,1 %

DIMENSIONS:

Dimensions (A x B x H) : 196 x 190 x 190 mm
Mounting centres (a x b) : 167 x 155 mm
Mounting diameter (ø) : 8 x 12 mm
Weight : 26,1 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 20A
Primary 230V (D circuit breaker) : 1 x 20A
Primary 400V (aM fuse(s)) : 1 x 10A
:
Secondary 230V : 1 x 8A
Other voltages : N.C.

OPTIONS:

No options found.