



EURM2002 - SINGLE-PHASE TRANSFORMER MULTI- VOLTAGE/2X24V - 2KVA - IP00



SKU: 14351
 Référence technique: S03F359V00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 61558-2-6 (24 V), EN 61558-2-4 (48 V), UL 5085-1, CSA C22.2
 Power : 2 kVA
 Primary voltage : multi-voltage (215-230-245-380-400-415-440-460-480)
 Secondary voltage : 2x24V (24-48V)
 :
 Protection : IP00
 Version : Transformer (UL-CSA certified safety & circuits separation)
 Inrush current : less than or equal to 25 In
 Heatings : 155°C
 Max. ambient T° : 40°C
 No load losses : 43,2 W
 Load losses : 106 W
 Voltage drop : 5 %
 UCC : 4 %
 Efficiency : 93,1 %

DIMENSIONS:

Dimensions (A x B x H) : 196 x 190 x 190 mm
 Mounting centres (a x b) : 167 x 155 mm
 Mounting diameter (ø) : 8 x 12 mm
 Weight : 26,1 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 20A
 Primary 230V (D circuit breaker) : 1 x 20A
 Primary 400V (aM fuse(s)) : 1 x 10A
 :
 Secondary 24V : 1 x 80A
 Secondary 48V : 1 x 40A
 Other voltages : N.C.

OPTIONS:

No options found.