


## EURM2501 - SINGLE-PHASE TRANSFORMER MULTI- VOLTAGE/2X115V - 2,5KVA - IP00



SKU: 15361  
Référence technique: S03F369J00

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : single-phase  
Certification(s) : EN 61558-2-4, UL C22.2, CSA 5085-1  
Power : 2,5 kVA  
Primary voltage : multi-voltage (215-230-245-380-400-415-440-460-480)  
Secondary voltage : 2x115V (115-230V)  
:  
Protection : IP00  
Version : Transformer (UL-CSA certified circuits separation)  
Inrush current : less than or equal to 25 I<sub>n</sub>  
Heatings : 155°C  
Max. ambient T° : 40°C  
No load losses : 48,5 W  
Load losses : 99 W  
Voltage drop : 3,8 %  
UCC : 3,6 %  
Efficiency : 94,4 %

### DIMENSIONS:

Dimensions (A x B x H) : 196 x 250 x 232 mm  
Mounting centres (a x b) : 167 x 175 mm  
Mounting diameter (ø) : 8 x 12 mm  
Weight : 31,5 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 25A  
Primary 230V (D circuit breaker) : 1 x 25A  
Primary 400V (aM fuse(s)) : 1 x 16A  
:  
Secondary 230V : 1 x 10A  
Other voltages : N.C.

### OPTIONS:

No options found.