



EURM2501 - SINGLE-PHASE TRANSFORMER MULTI- VOLTAGE/2X115V - 2,5KVA - IP00



SKU: 15361
 Référence technique: S03F369J00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 61558-2-4, UL C22.2, CSA 5085-1
 Power : 2,5 kVA
 Primary voltage : multi-voltage (215-230-245-380-400-415-440-460-480)
 Secondary voltage : 2x115V (115-230V)
 :
 Protection : IP00
 Version : Transformer (UL-CSA certified circuits separation)
 Inrush current : less than or equal to 25 I_n
 Heatings : 155°C
 Max. ambient T° : 40°C
 No load losses : 48,5 W
 Load losses : 99 W
 Voltage drop : 3,8 %
 UCC : 3,6 %
 Efficiency : 94,4 %

DIMENSIONS:

Dimensions (A x B x H) : 196 x 250 x 232 mm
 Mounting centres (a x b) : 167 x 175 mm
 Mounting diameter (ø) : 8 x 12 mm
 Weight : 31,5 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 25A
 Primary 230V (D circuit breaker) : 1 x 25A
 Primary 400V (aM fuse(s)) : 1 x 16A
 :
 Secondary 230V : 1 x 10A
 Other voltages : N.C.

OPTIONS:

No options found.