




EURM2502 - SINGLE-PHASE TRANSFORMER MULTI- VOLTAGE/2X24V - 2,5KVA - IP00



SKU: 14361
Référence technique: S03F369V00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-6 (24 V), EN 61558-2-4 (48 V), UL 5085-1, CSA C22.2
Power : 2,5 kVA
Primary voltage : multi-voltage (215-230-245-380-400-415-440-460-480)
Secondary voltage : 2x24V (24-48V)
:
Protection : IP00
Version : Transformer (UL-CSA certified safety & circuits separation)
Inrush current : less than or equal to 25 In
Heatings : 155°C
Max. ambient T° : 40°C
No load losses : 49,5 W
Load losses : 124 W
Voltage drop : 4,7 %
UCC : 3,8 %
Efficiency : 93,5 %

DIMENSIONS:

Dimensions (A x B x H) : 196 x 210 x 190 mm
Mounting centres (a x b) : 167 x 175 mm
Mounting diameter (ø) : 8 x 12 mm
Weight : 30,7 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 25A
Primary 230V (D circuit breaker) : 1 x 25A
Primary 400V (aM fuse(s)) : 1 x 16A
:
Secondary 24V : 1 x 100A
Secondary 48V : 1 x 50A
Other voltages : N.C.

OPTIONS:

No options found.