



EURM4001 - SINGLE-PHASE TRANSFORMER MULTI- VOLTAGE/2X115V - 4KVA - IP00



SKU: 15391
Référence technique: S03F399J00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-4, UL C22.2, CSA 5085-1
Power : 4 kVA
Primary voltage : multi-voltage (215-230-245-380-400-415-440-460-480)
Secondary voltage : 2x115V (115-230V)
:
Protection : IP00
Version : Transformer (UL-CSA certified circuits separation)
Inrush current : less than or equal to 25 In
Heatings : 155°C
Max. ambient T° : 40°C
No load losses : 52 W
Load losses : 133 W
Voltage drop : 3,2 %
UCC : 4 %
Efficiency : 95,6 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 220 x 265 mm
Mounting centres (a x b) : 200 x 160 mm
Mounting diameter (Ø) : 10 x 20 mm
Weight : 40,7 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 40A
Primary 230V (D circuit breaker) : 1 x 40A
Primary 400V (aM fuse(s)) : 1 x 20A
:
Secondary 230V : 1 x 16A
Other voltages : N.C.

OPTIONS:

No options found.