



EURMP2002 - SINGLE-PHASE TRANSFORMER MULTI- VOLTAGE/2X24V - 2KVA - IP21



SKU: 14355
Référence technique: 04F359V00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-6 (24 V), EN 61558-2-4 (48 V), UL 5085-1, CSA C22.2
Power : 2 kVA
Primary voltage : multi-voltage (215-230-245-380-400-415-440-460-480)
Secondary voltage : 2x24V (24-48V)
:
Protection : IP41-IK08
Version : Transformer (UL-CSA certified circuits separation)
Inrush current : less than or equal to 25 I_n
Heatings : 155°C
Max. ambient T° : 40°C
No load losses : 43,2 W
Load losses : 106 W
Voltage drop : 5 %
UCC : 4 %
Efficiency : 93,1 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 290 x 300 mm
Mounting centres (a x b) : 250 x 274 mm
Mounting diameter (∅) : 7 x 14 mm
Weight : 30,2 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 20A
Primary 230V (D circuit breaker) : 1 x 20A
Primary 400V (aM fuse(s)) : 1 x 10A
:
Secondary 24V : 1 x 80A
Secondary 48V : 1 x 40A
Other voltages : N.C.

OPTIONS:

No options found.