



EURP42 - SAFETY & SEPARATION TRANSFORMER 230-400/2X24V - 40VA - IP21



SKU: 12145
 Référence technique: 04Q15LV00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 61558-2-6
 Power : 40 VA
 Primary voltage : 230-400V
 Secondary voltage : 2x24V (24-48V)
 :
 Protection : IP41-IK08
 Version : safety & circuits separation
 Inrush current : less than or equal to 25 In
 Heatings : B (IEC60085)
 Max. ambient T° : 35°C
 No load losses : 3,5 W
 Load losses : 3,2 W
 Voltage drop : 7,4 %
 UCC : 6,3 %
 Efficiency : 85,7 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
 Mounting centres (a x b) : 200 x 224 mm
 Mounting diameter (ø) : 7x14 mm
 Weight : 3,9 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 0,5A
 Primary 230V (D circuit breaker) : 1 x 1A
 Primary 400V (aM fuse(s)) : 1 x 0,25A
 :
 Secondary 24V : 1 x 1,6A
 Secondary 48V : 1 x 0,8A

OPTIONS:

No options found.