



EURP402 - SAFETY & SEPARATION TRANSFORMER 230-400/2X24V - 400VA - IP21



SKU: 12265
Référence technique: 04Q26LV00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-6
Power : 400 VA
Primary voltage : 230-400V
Secondary voltage : 2x24V (24-48V)
:
Protection : IP41-IK08
Version : safety & circuits separation
Inrush current : less than or equal to 25 In
Heatings : B (IEC60085)
Max. ambient T° : 35°C
No load losses : 11,1 W
Load losses : 18 W
Voltage drop : 4,3 %
UCC : 3,8 %
Efficiency : 93,2 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
Mounting centres (a x b) : 200 x 224 mm
Mounting diameter (ø) : 7x14 mm
Weight : 9,3 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 4A
Primary 230V (D circuit breaker) : 1 x 4A
Primary 400V (aM fuse(s)) : 1 x 2A
:
Secondary 24V : 1 x 16A
Secondary 48V : 1 x 8A

OPTIONS:

No options found.