




EURP1602 - SAFETY & SEPARATION TRANSFORMER 230-400/2X24V - 1600VA - IP21



SKU: 12345
Référence technique: 04Q34LV00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-6
Power : 1600 VA
Primary voltage : 230-400V
Secondary voltage : 2x24V (24-48V)
:
Protection : IP41-IK08
Version : safety & circuits separation
Inrush current : less than or equal to 25 In
Heatings : F (IEC60085)
Max. ambient T° : 35°C
No load losses : 30,3 W
Load losses : 59,8 W
Voltage drop : 3,6 %
UCC : 3 %
Efficiency : 94,7 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 290 x 300 mm
Mounting centres (a x b) : 250 x 274 mm
Mounting diameter (ø) : 7x14 mm
Weight : 24,2 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 16A
Primary 230V (D circuit breaker) : 1 x 16A
Primary 400V (aM fuse(s)) : 1 x 8A
:
Secondary 24V : 1 x 63A
Secondary 48V : 1 x 32A

OPTIONS:

No options found.