



EURP2002 - SAFETY & SEPARATION TRANSFORMER 230-400/2X24V - 2KVA - IP21



SKU: 12355
Référence technique: 04Q35LV00

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-6
Power : 2 kVA
Primary voltage : 230-400V
Secondary voltage : 2x24V (24-48V)
:
Protection : IP41-IK08
Version : safety & circuits separation
Inrush current : less than or equal to 25 In
Heatings : F (IEC60085)
Max. ambient T° : 35°C
No load losses : 30,8 W
Load losses : 68,7 W
Voltage drop : 3,3 %
UCC : 3,1 %
Efficiency : 95,3 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 290 x 300 mm
Mounting centres (a x b) : 250 x 274 mm
Mounting diameter (Ø) : 7x14 mm
Weight : 26,9 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 20A
Primary 230V (D circuit breaker) : 1 x 20A
Primary 400V (aM fuse(s)) : 1 x 10A
:
Secondary 24V : 1 x 80A
Secondary 48V : 1 x 40A

OPTIONS:

No options found.